









High Pressure Pump Units HDP 30 Basic

Mobile high pressure unit with compact dimensions

High energy savings	High mobility	Other versions
Safe operation	Sturdy industrial engine	Application systems

HDP 30 Basic

Mobile electric unit with frequency converter for gun blasting work up to 29,000 psi

This mobile electric unit combines all the advantages of Hammelmann's tried-and-tested quality pumps with high economic efficiency, for the use of high pressure blasting guns in the pressure range of up to 29,000 psi.

- Long lifetime of all high-pressure components is ensured by optimal valve and sealing technology, the use of top quality materials and precise series production with state-of-the-art machines
- · Permanent corrosion resistance of the fluid end

- · High operational reliability and long maintenance intervals
- Hermetic sealing of the gear end with patented bellows sealing system
- · Leakage-free pump
- High reliability in continuous duty due to performance reserves by design

Areas of application







General gun blasting work Surface cleaning

Vessel cleaning Industrial cleaning

Cleaning of shuttering and scaffolding

Cleaning of vehicles and construction machines

Cleaning plaster molds and matrices

Accessories included in the scope of delivery



High-pressure spray gun SP 3000 E with electrical connector Hammelmann high-pressure spray guns are designed for demanding, industrial use. The ergonomically shaped handle and various extensions are easy to install.







Fan jet nozzle (15°)

High-pressure hose (65 ft.)

Control cable (82 ft.)

Optional accessories to expand the areas of application





The water tool for pros. Thanks to its compact and leight-weight design, enduring, fatigue-free work is possible. The Masterjet ensures a long service life thanks to the use of the patented HPS sealing system and robust components.



RD Mono (up to 2000 bar)

The simple rotor nozzle treats surfaces with high precision precisely and reliability at an operating pressure of up to 2000 bar.



Aquamat S


The smallest of our Aquamat tank cleaning units impresses with its patented HPS technology, which is also used in our Masterjet rotor jets.



Aquablast Basic E

Made for high class surface treatment, the electrically controlled Aquablast Basic E is a useful addition to a professional set-up that extends the possible range of applications with the HDP 30 Basic.

Easy to transport, with a wide range of customization options



Technical details

- · Robust chassis with protective frame
- Chassis with lockable swivel and fixed castors
- Holder for high-pressure hose, electric cable, and spray gun
- Frequency converter with integrated circuit breaker, display and water boost pressure monitoring
- Voltage supply 380 480 V, 50 / 60 Hz
- Connection via 5-pin 63 A CEE plug with 315 in. cable, RCD type B, ≥ 300 mA required
- · Electronically adjustable pressure control
- · Smooth motor start-up thanks to frequency converter
- Length: 60 in.
 Width: 34.1 in.
 Height: 57.1 in.
 Weight: 830 kg

- IE4 Motor Super Premium Efficiency
- PTC full motor protection
- · Water inlet with filter
- Ball valve for easy replacement of filters and water tools
- V-belt drive
- Dry unit, no bypass water
- Burst disc protection
- Tool box (removable)
- System with 1-point suspension
- Drive power: 40 hpDesign: 3-cylinder, standing



The HDP 30 Basic converts 97% of the shaft output into hydraulic energy.

Performance data

HDP	Flow rate	Operating pressure	Piston diameter
34 -	0.4 – 2.1 gpm	29,000 psi	12 mm
	0.6 – 2.9 gpm	22,000 psi	15 mm
33 -	0.8 – 4.2 gpm	14,500 psi	17,5 mm
	1.7 – 5.3 gpm	11,600 psi	22 mm
32	1.6 – 7.1 gpm	8,700 psi	24 mm
	1.8 - 8.5 gpm	7,250 psi	26 mm
	2.4 – 10.6 gpm	5,800 psi	30 mm

Factory Oelde















Hammelmann service worldwide

Subsidiaries in USA, China, Australia, Spain, France, Switzerland and 40 agents and distributors worldwide.



